

CANOPY + SHELF

T5 & T8 BI-PIN LINEAR

DISPLAY CASE LED FIXTURE

MAIN FEATURES

- 95 CRI Standard
- Designed for use in display cases and shelves; perfect for retrofitting jewelry showcases
- Standard design with rotatable end-caps for aiming
- Allows for daisy chain installation off one power supply

ELECTRICAL + CONTROLS

- Class 2 Low voltage connection, minimizing shock hazard
- Requires 24V external power supply (sold separately)
- Dimming available with dimming power supply; See power supply product sheet for dimming information

CONSTRUCTION

- Shatter resistant polycarbonate lens

OPTICS + PERFORMANCE

- Fixture life: 60,000 Hours (L70)

RATINGS + CERTIFICATIONS

- UL Type C Listed for damp locations
- RoHS-compliant
- NSF Certified

WARRANTY

- 5-year warranty



Nominal Length	Max. Overall Length (MOL)		Output	Power (Watts)
	T5	T8		
60"	57.6"	59.6"	3400	30.0
			2000	18.0
			1000	9.0
48"	45.8"	47.8"	3000	26.0
			1600	15.0
			1000	9.0
36"	34.0"	35.8"	2600	23.0
			1200	11.0
			600	5.5
24"	22.2"	23.8"	2000	18.0
			1000	9.0
			500	4.5
18"	17.8"	17.8"	600	5.5
12"	11.7"	11.7"	500	4.5

*Output and power in table to left is shown at 3500K. Use multiplier table below for correction factors.

CCT	Multiplier
2700K	0.93
3000K	0.97
3500K	1.0
4000K	1.02
5000K	1.03


T5




T8



T5



T8



Ordering Information

Example: CST5/48/D/930/1600

Fixture	Lens	CRI + CCT	Length	Lumen Output
CST5	D - Diffused	927 - 90+ CRI, 2700K	12	500
CST8		930 - 90+ CRI, 3000K	18	600
		935 - 90+ CRI, 3500K	24	2000
		940 - 90+ CRI, 4000K		1000
		950 - 90+ CRI, 5000K		500
			36	2600
				1200
				600
			48	3000
				1600
				1000
			60	3400
				2000
				1000

*Consult factory for lead time and availability