Modules

YM20 | YM24 XM20 | XM24 | XM30



PROJECT TYPE

SPECIFICATION

\ 120 V

\ 50,000 Hours (L70)

\ Integrated driver with Xm modules

GU 24 base

\ UL Certified

\ RoHs-compliant

\ Dry location rating

\ Contains no lead or mercury

\ Designed for use with Solais downlights, multiples and cylinders

\ VioLight and MonoWhite* color rendering enhancements available

\ * 90+ High CRI available. Consult factory for availability.

To order, replace 'K' in CCT designation with 'h' in code below.









Ordering Information Example: Xm24/25/30K/2000/WH/SN ССТ Lumens Exterior Finish Options + Accessories Fixture **Beam Spread** WH - White TS - Tapered Snoot 25K* Xm20 15c 700 - 2000 BK - Black Ym20 27K HL - Honeycomb Louver 25c SV - Silver 30K SL - Linear Spread 40c PW* - Perfect 30m* SP - Prismatic Spread 15 White 30v SS - Solite Spread 25 More Accessories Available 40 35m* Xm24 15c 25K* 1400 - 2400 25c Ym24 27K 40c 30K 15 30m* 25 30v 35K* 40 35m* 40K* 15c 25K* Xm30 2300 - 3500 27K 25c 40c 30K



30m* 30v

35K*

35m*

15

25

40

WARNING: Not for use in fully enclosed luminaires. Risk of electric shock. Use in an indoor, dry location only. This device is not intended for use with emergency exit fixtures or emergency exit lights. May not be compatible with all dimmers; please visit solais.com\dimming for up-to-date dimmer compatibility information.

NOTES: This device complies with Part 15 of the FCC Rule. This product may cause interference with other devices. If interference occurs, change the locations of the products involved. **Compatible on 120v systems.**



Luxiance utilizes active cooling to remove heat from the LED system - allowing Solais LED lamps to operate cooler, resulting in superior life, light output, and performance.



VioLight radiates superior quality, enhancing colors in merchandise, making colors more vibrant and offering a truly competitive LED replacement for CMH-like crispness.





