

RDC Mid Temp

REACH-IN DOOR RETROFIT MEDIUM TEMPERATURE COOLERS

PROJECT _____

TYPE _____

SPECIFICATION _____

- 95 CRI Standard
- Class 2 low voltage fixture
- 50,000 Hours (L70)
- UL Listed
- NSF certified
- RoHs-compliant
- IP66 wet location rated
- Contain no lead or mercury
- Dimming based on power supply
- Single-piece extrusion
- Shatter-resistant housing
- Wiring box accessory available
- Ideal for reach-in freezer and coolers with an external power supply



Ordering Information

Example: RDC50/L/940/3000/BK/BB-UB

Fixture	Length	Throw	CCT	Lumens	Color	Accessories
RDC	50 60	L - Lambertian	930 935 940	3000	BK - Black	{blank} - Upper + lower bracket built in; 1 center bracket included CB - Additional Center Bracket WB - Wiring Box (Note: adding a wiring box increases the overall length by 1.4")

Note: Data below based on 4000K. Use output multipliers on right to calculate data for other color temperatures.

Fixture	Nominal Length	Lumen Output	Power (Watts)	MOL (inches)	Weight	CRI	CCT	Multiplier
RDC	50"	3000	21	50 ½	12 oz.	95	3000K	0.98
	60"			56 ½	12.5 oz.		3500K	1.00
							4000K	1.01

