

R-XFR

X-SERIES | RETROFIT FULLY RECESSED MULTIPLE


SOLAIS[®]

PROJECT

TYPE

SPECIFICATION

- Upgrade to modular Solais multiples without complicated re-installation
- **Replacement for:**
 - Amerlux Hornet LED (AH)
 - Amerlux Cylindrix CMH (AC1)
 - Amerlux Cylindrix III Mini LED (ACM)
 - Amerlux Cylindrix Mini Master (AHT)
 - Amerlux Hornet Trimless (AHT)
- 120 V
- 0-10 V*, Triac and ELV dimming
- 50,000 Hours (L70)
- Integrated driver
- RoHS-compliant
- Dry location rating
- Certified to UL Standards
- Contain no lead or mercury
- Non-IC Rated. Insulation must be kept 3" from sides and 1" above housing
- VioLight and *MonoWhite color rendering enhancements available
- *90+ High CRI available. To order, replace 'K' in CCT designation with 'h' in ordering code.



R-XFR11

X-SERIES | 1-HEAD

RETROFIT RECESSED MULTIPLE



SOLAIS®

PROJECT


TYPE

SPECIFICATION


- All Types



- Type: AHT
- Weight without module: 2.5 lb



- Type: AC1, ACM, AH
- Weight without module: 2.5 lb



Ordering Information

Example: R-XFR11/ACM/Xm20/25/30K/2400/WH/WH/SL

Fixture	Type	Module	Beam Spread	CCT / Lumens	Options + Accessories
R-XFR11	AC1 ACM AH AHT	Xm20	COB-optic	25K* / 1000 15c 27K / 1050 25c 30K / 1100 40c 35K* / 1100 60c 35m* / 1100 40K* / 1100	Module Options HL - Honeycomb Louver SL - Linear Spread SP - Prismatic Spread More Accessories Available
				25K* / 1300 27K / 1400 30K / 1500 30m* / 1500 35K* / 1500 35m* / 1500 40K* / 1500	Fixture Options 010 - 0-10 V Dimming* EM - Emergency Backup Microinverter*
				25K* / 1800 27K / 1900 30K / 2000 30m* / 2000 35K* / 2000 35m* / 2000 40K* / 2000	Trim Finish Die-cast, Powder Coated WH / WH - White Module, Interior + Flange BK / BK - Black Module, Interior + Flange BK / WH* - Black Module + Interior, White Flange PW / PW* - Perfect White Module, Interior + Flange BK / PW* - Black Module + Interior, Perfect White Flange
			Multi-optic	27K / 1400 30K / 1450	
			15m	30v / 1450	
			25m	35K* / 1450	
			40m	40K* / 1450	
			60m		
			Specialty	27K / 750 30K / 750	
			10c		
			Dim-to-Warm	(2700K to 1800K)	
			25c	D27 / 1000	
			40c		

*Consult factory for lead time and availability

R-XFR12

X-SERIES | 2-HEAD

RETROFIT RECESSED MULTIPLE


SOLAIS®

PROJECT


TYPE

SPECIFICATION


- All Types



- Type: AHT
- Weight w/o module: 4 lb



- Type: AC1, ACM, AH
- Weight w/o module: 4 lb



Ordering Information

Example: R-XFR12/ACM/Xm20/25-25/30K/1100/WH/WH/SL-SL

		1		2		1		2			
Fixture	Type	Module	Beam Spread	CCT	Lumens	Options + Accessories					
R-XFR12	AC1 ACM AH AHT	Xm20	COB-optic	25K*	1000	Module Options					
			15c	27K	1050	HL - Honeycomb Louver					
			25c	30K	1100	SL - Linear Spread					
			40c	30m*	1100	SP - Prismatic Spread					
			60c	35K*	1100	More Accessories Available					
				35m*	1100	Fixture Options					
				40K*	1100	010 - 0-10 V Dimming*					
						EM - Emergency Backup					
						Microinverter*					
						Trim Finish					
						Die-cast, Powder Coated					
						WH / WH - White Module, Interior + Flange					
						BK / BK - Black Module, Interior + Flange					
						BK / WH* - Black Module + Interior, White Flange					
						PW / PW* - Perfect White Module, Interior + Flange					
						BK / PW* - Black Module + Interior, Perfect White Flange					



*Consult factory for lead time and availability

R-XFR13

X-SERIES | 3-HEAD

RETROFIT RECESSED MULTIPLE


SOLAIS[®]

PROJECT


TYPE

SPECIFICATION

▪ All Types



- Type: AHT
- Weight w/o module: 5.5 lb



- Type: AC1, ACM, AH
- Weight w/o module: 5.5 lb

Ordering Information

Example: R-XFR13/ACM/Xm20/25-25-25/30K/1100/WH/WH/SL-SL-SL

1 - 2 - 3

1 - 2 - 3


Fixture R-XFR13	Type AC1 ACM AH AHT	Module Xm20	Beam Spread COB-optic	CCT / Lumens
			15c	25K* / 1000
			25c	27K / 1050
			40c	30K / 1100
			60c	30m* / 1100
				35K* / 1100
				35m* / 1100
				40K* / 1100
				25K* / 1300
				27K / 1400
				30K / 1500
				30m* / 1500
				35K* / 1500
				35m* / 1500
				40K* / 1500
				25K* / 1800
				27K / 1900
				30K / 2000
				30m* / 2000
				35K* / 2000
				35m* / 2000
				40K* / 2000
			Multi-optic	27K / 1400
			15m	30K / 1450
			25m	30v / 1450
			40m	35K* / 1450
			60m	40K* / 1450
			Specialty	27K / 750
			10c	30K / 750
			Dim-to-Warm	(2700K to 1800K)
			25c	D27 / 1000
			40c	

Trim Finish

Die-cast, Powder Coated
 WH / WH - White Module, Interior + Flange
 BK / BK - Black Module, Interior + Flange
 BK / WH* - Black Module + Interior, White Flange
 PW / PW* - Perfect White Module, Interior + Flange
 BK / PW* - Black Module + Interior, Perfect White Flange

Options + Accessories

Module Options
 HL - Honeycomb Louver
 SL - Linear Spread
 SP - Prismatic Spread
 More Accessories Available
 Fixture Options
 010 - 0-10 V Dimming*
 EM - Emergency Backup
 Microinverter*



*Consult factory for lead time and availability

R-XFR14

X-SERIES | 4-HEAD

RETROFIT RECESSED MULTIPLE


SOLAIS®

PROJECT


TYPE

SPECIFICATION


All Types



- Type: AHT
- Weight w/o module: 7 lb



- Type: AC1, ACM, AH
- Weight w/o module: 7 lb



Ordering Information

Example: R-XFR14/ACM/Xm20/25-25-25/30K/1100/WH/WH/SL-SL-SL

1 - 2 - 3 - 4				1 - 2 - 3 - 4			
Fixture	Type	Module	Beam Spread	CCT / Lumens	Options + Accessories		
R-XFR14	AC1 ACM AH AHT	Xm20	COB-optic	25K* / 1000	Module Options HL - Honeycomb Louver SL - Linear Spread SP - Prismatic Spread More Accessories Available		
			15c	27K / 1050			
			25c	30K / 1100	Fixture Options 010 - 0-10 V Dimming* EM - Emergency Backup Microinverter*		
			40c	30m* / 1100			
			60c	35K* / 1100	Trim Finish Die-cast, Powder Coated WH / WH - White Module, Interior + Flange BK / BK - Black Module, Interior + Flange BK / WH* - Black Module + Interior, White Flange PW / PW* - Perfect White Module, Interior + Flange BK / PW* - Black Module + Interior, Perfect White Flange		
				35m* / 1100			
				40K* / 1100			
				25K* / 1300			
				27K / 1400			
				30K / 1500			
				30m* / 1500			
				35K* / 1500			
				35m* / 1500			
				40K* / 1500			
				25K* / 1800			
				27K / 1900			
				30K / 2000			
				30m* / 2000			
				35K* / 2000			
				35m* / 2000			
				40K* / 2000			
			Multi-optic	27K / 1400			
			15m	30K / 1450			
			25m	30v / 1450			
			40m	35K* / 1450			
			60m	40K* / 1450			
			Specialty	27K / 750			
			10c	30K / 750			
			Dim-to-Warm	(2700K to 1800K)			
			25c	D27 / 1000			
			40c				



*Consult factory for lead time and availability

R-XFR

X-SERIES | RETROFIT FULLY RECESSED MULTIPLE

PROJECT

TYPE

SPECIFICATION

PHOTOMETRIC DETAILS | baseline X output multiplier X cri-cct multiplier = final output

COB OPTIC: Baseline for 23 W,
2000 lumens, 80+ CRI, 3000K

Xm20/10c/30K/750

Input Power: 11.2 W
Lumens: 749 lm
Efficacy: 67 lm/W
CBCP: 11648
Beam Angle: 10.6°
Field Angle: 20.8°
Spacing Criteria: 0.19

∠	0°	45°	90°
0°	11648	11648	11648
5°	6264	6089	5926
10°	1275	1202	1208
15°	502	487	477
20°	215	210	202
25°	97	96	93
30°	54	56	52
35°	35	34	31
40°	21	20	19
45°	10	9	10

Xm20/15c/30K/2000

Input Power: 22.7 W
Lumens: 1978 lm
Efficacy: 87 lm/W
CBCP: 15892
Beam Angle: 16.2°
Field Angle: 33.7°
Spacing Criteria: 0.28

∠	0°	45°	90°
0°	15871	15871	15871
5°	12935	12636	12231
10°	5971	5675	5433
15°	2207	2176	2116
20°	1027	977	936
25°	484	473	436
30°	246	252	230
35°	157	157	146
40°	122	115	109
45°	106	99	88

Xm20/25c/30K/2000

Input Power: 22.8 W
Lumens: 1821 lm
Efficacy: 80 lm/W
CBCP: 6729
Beam Angle: 23.3°
Field Angle: 50.4°
Spacing Criteria: 0.41

∠	0°	45°	90°
0°	6729	6729	6729
5°	5937	5855	5779
10°	4081	3975	3895
15°	2348	2291	2231
20°	1274	1228	1203
25°	710	683	676
30°	427	411	404
35°	280	270	265
40°	198	189	187
45°	135	124	124

Xm20/40c/30K/2000


Input Power: 22.4 W
Lumens: 1823 lm
Efficacy: 81 lm/W
CBCP: 3312
Beam Angle: 39.7°
Field Angle: 72.4°
Spacing Criteria: 0.72

∠	0°	45°	90°
0°	3310	3310	3310
5°	3180	3206	3216
10°	2795	2843	2868
15°	2227	2283	2320
20°	1591	1636	1682
25°	1021	1047	1095
30°	603	618	655
35°	347	355	378
40°	207	212	224
45°	131	133	140

Xm20/60c/30K/2000

Input Power: 22.9 W
Lumens: 1990 lm
Efficacy: 87 lm/W
CBCP: 1121
Beam Angle: 53.3°
Field Angle: 91.4°
Spacing Criteria: 1.00

∠	0°	45°	90°
0°	1118	1118	1118
5°	1089	1085	1076
10°	1030	1018	997
15°	937	922	887
20°	799	770	737
25°	632	598	576
30°	460	431	414
35°	308	287	279
40°	201	187	180
45°	126	117	108



3'	0.56' D; 906 FC	0.85' D; 1234 FC	1.23' D; 523 FC	2.16' D; 257 FC	3.01' D; 87 FC
6'	1.11' D; 227 FC	1.70' D; 309 FC	2.47' D; 131 FC	2.47' D; 64 FC	6.02' D; 22 FC
9'	1.67' D; 101 FC	2.55' D; 137 FC	3.70' D; 58 FC	6.49' D; 29 FC	9.03' D; 10 FC
12'	2.23' D; 57 FC	3.41' D; 77 FC	4.94' D; 33 FC	8.65' D; 16 FC	12.04' D; 5 FC
15'	2.78' D; 36 FC	4.26' D; 49 FC	6.17' D; 21 FC	10.82' D; 10 FC	15.06' D; 4 FC

MULTI-OPTIC: Baseline for 16 W,
1450 lumens, 80+ CRI, 3000K

Xm20/15m/30K/1450

Input Power: 16.2 W
Lumens: 1595 lm
Efficacy: 98 lm/W
CBCP: 18848
Beam Angle: 12.7°
Field Angle: 28.0°
Spacing Criteria: 0.22

∠	0°	45°	90°
0°	18848	18848	18848
5°	11986	12047	12378
10°	4597	4761	4865
15°	1318	1708	1443
20°	449	521	469
25°	227	262	235
30°	165	172	160
35°	102	112	106
40°	70	76	83
45°	37	34	36

Xm20/25m/30K/1450


Input Power: 16.1 W
Lumens: 1525 lm
Efficacy: 95 lm/W
CBCP: 5928
Beam Angle: 26.1°
Field Angle: 49.2°
Spacing Criteria: 0.46

∠	0°	45°	90°
0°	5928	5928	5928
5°	5307	5357	5371
10°	3847	3970	4026
15°	2233	2393	2486
20°	1081	1179	1266
25°	501	554	600
30°	247	278	298
35°	134	152	160
40°	82	89	91
45°	48	54	55

Xm20/40m/30K/1450

Input Power: 16.2 W
Lumens: 1434 lm
Efficacy: 89 lm/W
CBCP: 2886
Beam Angle: 38.2°
Field Angle: 69.9°
Spacing Criteria: 0.69

∠	0°	45°	90°
0°	2886	2886	2886
5°	2813	2786	2753
10°	2422	2405	2364
15°	1922	1923	1882
20°	1409	1408	1385
25°	902	915	905
30°	513	532	524
35°	282	292	291
40°	155	161	161
45°	83	84	84



3'	0.67' D; 1466 FC	1.39' D; 461 FC	2.08' D; 225 FC
6'	1.33' D; 367 FC	2.78' D; 115 FC	4.16' D; 56 FC
9'	2' D; 163 FC	4.17' D; 51 FC	6.23' D; 25 FC
12'	2.66' D; 92 FC	5.56' D; 29 FC	8.31' D; 14 FC
15'	3.33' D; 59 FC	6.95' D; 18 FC	10.39' D; 9 FC

CRI-CCT MULTIPLIER

CRI	CCT	Multiplier
8 (80+)	2200K	0.86
	2500K	0.91
	2700K	0.96
	3000K	1.00
	3500K	1.03
9 (90+)	4000K	1.05
	2200K	0.70
	2500K	0.77
	2700K	0.83
	3000K	0.86
M (MonoWhite)	3500K	0.89
	4000K	0.91
V (VioLight)	3000K	0.86
	3500K	0.88

OUTPUT MULTIPLIER

Package	Multiplier
17 W 1500 lm Xm20 COB-optic	0.82
13 W 1100 lm Xm20 COB-optic	0.77

R-XFR

X-SERIES | RETROFIT FULLY RECESSED MULTIPLE











PROJECT

TYPE

SPECIFICATION




TM30 COLOR REPORTS

- 3000K with 80+ CRI
 - $R_f = 84$; $R_g = 94$
 - $R_A = 82$; $R_9 = 11$
- 3000K with 90+ CRI
 - $R_f = 92$; $R_g = 100$
 - $R_A = 93$; $R_9 = 56$
- 3000K with 97+ CRI
 - $R_f = 96$; $R_g = 104$
 - $R_A = 97$; $R_9 = 98$
- 3000K with MonoWhite
 - $R_f = 91$; $R_g = 100$
 - $R_A = 91$; $R_9 = 42$



DIM TO WARM DETAILS | Dim to warm only available with 25° and 40° beam spreads; 90+CRI


- 2700K to 1800K with 90+ CRI
 - $R_f = 92$; $R_g = 100$
 - $R_A = 93$; $R_9 = 57$



Xm20/25c/30K/1000

Input Power: 15.7 W
Lumens: 1012 lm
Efficacy: 65 lm/W
CBCP: 3537
Beam Angle: 28.0°
Field Angle: 53.4°
Spacing Criteria: 0.50

∠	0°	45°	90°
0°	3530	3530	3530
5°	3328	3305	3281
10°	2575	2546	2499
15°	1630	1619	1592
20°	894	890	874
25°	441	435	433
30°	222	216	217
35°	106	102	100
40°	43	40	40
45°	9	9	9



Xm20/40c/30K/1000

Input Power: 15.6 W
Lumens: 967 lm
Efficacy: 62 lm/W
CBCP: 2231
Beam Angle: 36.1°
Field Angle: 65.0°
Spacing Criteria: 0.65

∠	0°	45°	90°
0°	2225	2225	2225
5°	2148	2142	2128
10°	1880	1850	1824
15°	1434	1394	1366
20°	953	920	896
25°	563	540	527
30°	310	296	290
35°	157	152	149
40°	75	72	70
45°	31	30	29

WARNING: Not for use in fully enclosed luminaires. Risk of electric shock. Use in an indoor, dry location only. This device is not intended for use with emergency exit fixtures or emergency exit lights. May not be compatible with all dimmers; please visit solais.com/dimming for up-to-date dimmer compatibility information.
NOTES: This device complies with Part 15 of the FCC Rule. This product may cause interference with other devices. If interference occurs, change the locations of the products involved. **Compatible on 120v systems.**