

ORDERING CODE BREAKDOWN

SPECIFICATION CODE

SPECIFIER

PROJECT TYPE

MEMO

SCATTO | SCLT 48V TRACK SYSTEM

LONG RECESSED FLANGELESS | GYPSUM

MAIN FEATURES

- Designed for recessed flangeless applications with %" gypsum
- Designed for linear luminaires to sit flush and trackhead adapters to recess into the track.

(SC2 mounting required)

- Great for use in architectural and highend applications
- Field-cuttable for custom lengths





Scatto Track

SC31-LT-4 - 4ft. Recessed flangeless, gypsum

SC31-LT-8 - 8ft. Recessed flangeless, gypsum

SC-LX-ECC - End Cap SC-LX-ECF - End Cap, feedable

SC31-RT Accessories

SC-LX-TCV - Track Cover

SC-LT-HMC - Horizontal Mechanical Corner Joint SC-LT-EMC - External Vertical Mechanical Corner Joint SC-LT-IMC - Internal Vertical Mechanical Corner Joint SC-UM-SRB - Straight Reinforcing Bracket

Finish

BK - Black

SC-UM-TCT - Conductor Cutting Tool

RATINGS + CERTIFICATIONS

- UL Certified for dry locations
- RoHs-compliant
- Designed for use with Solais® Scatto™ fixtures and components
- ELECTRICAL + SAFETY
- = 48V, +/- 2A
- 96W maximum load

CONSTRUCTION + FINISH

- Extruded aluminum construction standard finish in black (RAL 9005)
- Insulated extruded body in PVC
- Solid copper conductors

WARRANTY


3-year warranty




SC31 Connectors

SC31-UM-EFR - End feed, Right Polarity SC31-UM-EFL - End feed, Left Polarity SC31-UM-SJC - Straight Joining Connector SC31-UM-SIC - Straight Insolating Connector SC31-UM-LFI - 'L' live feed, Inner Polarity SC31-UM-LFO - 'L' live feed, Outer Polarity SC31-UM-TOL - 'T' live feed, Outer/Left Polarity SC31-UM-TOR - 'T' live feed, Outer/Right Polarity SC31-UM-TIL - 'T' live feed, Inner/Left Polarity SC31-UM-TIR - 'T' live feed, Inner/Right Polarity

SC31-UM-XFC - 'X' live feed








SC31-UM-ACR - Adjustable Connector







SPECIFICATION CODE

PROJECT

SCATTO | SCLT

48V TRACK SYSTEM LONG RECESSED FLANGELESS | GYPSUM

SC-LX-ECC End Cap Metal end cap; Compatible with SCLT, SCLH and SCTM SC-LX-ECF End Cap Metal end cap, feedable Compatible with SCLT, SCLH and SCTM SC-LX-TCV Aesthetic Track Cover PMMA; Field cuttable, 118 ½" | 3000 mm SC-LT-HMC Horizontal Mechanical Corner Joint РММА; SC-IT-FMC External Vertical Mechanical Corner Joint PMMA SC-LT-IMC Internal Vertical Mechanical Corner Joint PMMA: SC-UM-SRB Reinforcing Bracket Aluminum joining connector

TYPE

