

SCATTO | SCRF

48V TRACK SYSTEM
RECESSED WITH FLANGE

MAIN FEATURES

- Designed for recessed mount with flange applications
- Designed for linear luminaires to extend past the track and trackhead adapters to sit flush
- Great for use in architectural and high-end applications
- Field-cutable for custom lengths




Ordering Information



Scatto Type + Length

SC31-RF-4 - 4ft. Recessed with flange
SC31-RF-8 - 8ft. Recessed with flange




Sc31 Accessories

SC-RF-ECC - End Cap
SC-UM-TCT - Conductor Cutting Tool
SC-RF-LMB - 'L' Mechanical Bracket



Sc31 Connectors

SC31-UM-EFR - End feed, Right Polarity
SC31-UM-EFL - End feed, Left Polarity
SC31-UM-SJC - Straight Joining Connector
SC31-UM-SIC - Straight Isolating Connector
SC31-UM-LFI - 'L' live feed, Inner Polarity
SC31-UM-LFO - 'L' live feed, Outer Polarity
SC31-UM-TOL - 'T' live feed, Outer/Left Polarity
SC31-UM-TOR - 'T' live feed, Outer/Right Polarity
SC31-UM-TIL - 'T' live feed, Inner/Left Polarity
SC31-UM-TIR - 'T' live feed, Inner/Right Polarity
SC31-UM-XFC - 'X' live feed
SC31-UM-ACR - Adjustable Connector



Scatto Suspension

SC-UM-TCC - Ceiling Clamp
SC-UM-LJB - Long Joining Bracket
SS-UM-SEG - Side Exit Gripper
SS-UM-SMC - Surface Mount Cable Coupler
SS-UM-DLG - Double Looping-Gripper
SS-UM-ACB - Barrel End Aircraft Cable, 20 ft.
SS-UM-ACL - Loop End Aircraft Cable, 20 ft.
SS-UM-CPC - Ceiling Cup with Ceiling Bracket
SS-RF-RCC - Recessed Clamp

RATINGS + CERTIFICATIONS

- UL Certified for dry locations
- RoHS-compliant
- Designed for use with Solais® Scatto™ fixtures and components

ELECTRICAL + SAFETY



- 48V, +/- 2A
- 96W maximum load









CONSTRUCTION + FINISH









- Extruded aluminum construction standard finish in black (RAL 9005)
- Insulated extruded body in PVC
- Solid copper conductors

















WARRANTY









- 3-year warranty








Accessories		
SC-RF-ECC End Cap <i>Metal end cap;</i>		
SC-RF-LMB 'L' Mechanical Bracket <i>Steel; For suspension</i>		
SC-SX-TCV Aesthetic Track Cover <i>PMMA; Field cuttable, 118 1/2" 3000 mm</i> <i>Compatible with SCST, SCRT, SCSH, SCRF, and SCSM</i>		
SC-UM-SRB Reinforcing Bracket <i>Aluminum joining connector</i>		

Scatto Connector		
SC31-UM-EFL End feed, Left Polarity <i>Polycarbonate body, copper alloy contacts</i>		
SC31-UM-EFR End feed, Right Polarity <i>Polycarbonate body, copper alloy contacts</i>		
SC31-UM-SJC Straight Joining Connector <i>Polycarbonate body, copper alloy contacts</i>		
SC31-UM-SIC Joining Insulating Connector, Mechanical <i>Polycarbonate body</i>		

Scatto Connector		
SC31-UM-LFI 'L' live feed, Inner Polarity <i>Polycarbonate body, copper alloy contacts</i>		
SC31-UM-LFO 'L' live feed, Outer Polarity <i>Polycarbonate body, copper alloy contacts</i>		
SC31-UM-TOL 'T' live feed, Outer/Left Polarity <i>Polycarbonate body, copper alloy contacts, 2 PMMA covers</i>		
SC31-UM-TOR 'T' live feed, Outer/Right Polarity <i>Polycarbonate body, copper alloy contacts, 2 PMMA covers</i>		
SC31-UM-TIL 'T' live feed, Inner/Left Polarity <i>Polycarbonate body, copper alloy contacts, 2 PMMA covers</i>		
SC31-UM-TIR 'T' live feed, Inner/Right Polarity <i>Polycarbonate body, copper alloy contacts, 2 PMMA covers</i>		
SC31-UM-XFC 'X' live feed <i>Polycarbonate body, copper alloy contacts, 3 PMMA covers</i>		
SC31-UM-ACR Adjustable Connector <i>Polycarbonate body, copper alloy contacts</i>		

Scatto Suspension		
SC-UM-TCC Ceiling Clamp <i>Steel; Recommended for use with SS-U-SEG</i>		
SC-UM-LJB Long Joining Bracket <i>Steel; For aircraft Cable Suspension; Recommended for use with SS-U-SEG</i>		
SS-UM-CPC Ceiling Cup <i>with ceiling bracket and screw gripper for use with cable suspension</i>		
SC-RF-RCC Recessed Clamp <i>Zinc plated steel clamp and screw</i>		

Track Suspension Accessories		
SS-UM-TSC T-bar Seismic Suspension Clamp <i>For use where local code requires direct connection to the ceiling. Ceiling-supported clip for 15/16" T-bar</i>		
SS-UM-ACL Aircraft Cable with Loop <i>20 feet of 1/16" galvanized cable. Recommended for use with SS-UM-SEG.</i>		
SS-UM-ACB Aircraft Cable with Barrel <i>20 feet of 1/16" galvanized cable. Recommended for use with SS-UM-SEG.</i>		
SS-UM-SEG Side Cable Exit Gripper <i>For use with 3/64" or 1/16" threaded cable only. Recommended for use with SS-UM-ACL or SS-UM-ACB.</i>		
SS-UM-SMC Surface Mount Cable Coupler <i>2-part non-adjustable cable coupler. Recommended for use with SS-UM-ACB.</i>		
SS-UM-DLG Double Mechanism Looping Gripper <i>Double-ended gripper with double side cable exits for use with 3/64" or 1/16" threaded cable only.</i>	