

PROJECT _____ TYPE _____

SPECIFIER _____ MEMO _____

ORDERING CODE BREAKDOWN _____

SCATTO | SCSM

48V TRACK SYSTEM
SHORT RECESSED FLANGELESS | MILLWORK

MAIN FEATURES

- Designed for recessed flangeless applications with millwork
- Designed for linear luminaires to extend past the track and trackhead adapters to sit flush
- Great for use in architectural and high-end applications
- Field-cutable for custom lengths



Ordering Information

_____ / _____

Finish
BK - Black

Scatto Type + Length

SC31-SM-4 - 4ft. Recessed flangeless, millwork
SC31-SM-8 - 8ft. Recessed flangeless, millwork

_____ / _____

Finish
BK - Black

SC31-SM Accessories

SC-SX-ECC - End Cap
SC-SX-ECF - End Cap, feedable
SC-UM-TCT - Conductor Cutting Tool

RATINGS + CERTIFICATIONS

- UL Certified for dry locations
- RoHS-compliant
- Designed for use with Solais® Scatto™ fixtures and components

ELECTRICAL + SAFETY

- 48V, +/- 2A
- 96W maximum load

CONSTRUCTION + FINISH

- Extruded aluminum construction standard finish in black (RAL 9005)
- Insulated extruded body in PVC
- Solid copper conductors

WARRANTY



- 3-year warranty

_____ / _____














Finish
BK - Black

SC31 Connectors

SC31-UM-EFR - End feed, Right Polarity
SC31-UM-EFL - End feed, Left Polarity
SC31-UM-SJC - Straight Joining Connector
SC31-UM-SIC - Straight Insulating Connector
SC31-UM-LFI - 'L' live feed, Inner Polarity
SC31-UM-LFO - 'L' live feed, Outer Polarity
SC31-UM-TOL - 'T' live feed, Outer/Left Polarity
SC31-UM-TOR - 'T' live feed, Outer/Right Polarity
SC31-UM-TIL - 'T' live feed, Inner/Left Polarity
SC31-UM-TIR - 'T' live feed, Inner/Right Polarity
SC31-UM-XFC - 'X' live feed
SC31-UM-ACR - Adjustable Connector



PROJECT _____ TYPE _____

Accessories			Scatto Connector		
SC-SX-ECC End Cap <i>end cap, closed;</i> <i>Compatible with SCST and SCSM</i>			SC31-UM-LFI 'L' live feed, Inner Polarity <i>Polycarbonate body,</i> <i>copper alloy contacts</i>		
SC-SX-ECF End Cap <i>end cap, feedable</i> <i>Compatible with SCST and SCSM</i>			SC31-UM-LFO 'L' live feed, Outer Polarity <i>Polycarbonate body,</i> <i>copper alloy contacts</i>		
SC-SX-TCV Aesthetic Track Cover <i>PMMA; Field cuttable,</i> <i>118 3/4" 3000 mm</i> <i>Compatible with SCST, SCRT, SCSH,</i> <i>SCRF, and SCSM</i>			SC31-UM-TOL 'T' live feed, Outer/Left Polarity <i>Polycarbonate body, copper alloy</i> <i>contacts, 2 PMMA covers</i>		
SC31-UM-EFL End feed, Left Polarity <i>Polycarbonate body,</i> <i>copper alloy contacts</i>			SC31-UM-TOR 'T' live feed, Outer/Right Polarity <i>Polycarbonate body, copper alloy</i> <i>contacts, 2 PMMA covers</i>		
SC31-UM-EFR End feed, Right Polarity <i>Polycarbonate body,</i> <i>copper alloy contacts</i>			SC31-UM-TIL 'T' live feed, Inner/Left Polarity <i>Polycarbonate body, copper alloy</i> <i>contacts, 2 PMMA covers</i>		
SC31-UM-SJC Straight Joining Connector <i>Polycarbonate body,</i> <i>copper alloy contacts</i>			SC31-UM-TIR 'T' live feed, Inner/Right Polarity <i>Polycarbonate body, copper alloy</i> <i>contacts, 2 PMMA covers</i>		
SC31-UM-SIC Joining Insulating Connector, Mechanical <i>Polycarbonate body</i>			SC31-UM-XFC 'X' live feed Connector <i>Polycarbonate body, copper alloy</i> <i>contacts, 3 PMMA covers</i>		
			SC31-UM-ACR Adjustable Connector <i>Polycarbonate body,</i> <i>copper alloy contacts</i>		